


Unit 75, Whitehill & Bordon Enterprise Park Budds Lane, Bordon, Hampshire GU35 0FJ

Email: sales@polymax.co.uk Tel: +44 (0)1420 474 123





Rectangular Dock Bumper TPX 490L x 80W x 90H

Product SKU: 6009403

Durable Tyrecord Hi-Fibre material provides the longest lasting protection to the HGV or loading bay.

These fenders are commonly found on the HGV trailer to prevent damage to the metalwork of the vehicle. The Tyrecord Hi-Fibre material is an extremely strong and durable rubber. The thin rectangular design is a suitable shape to fix along the bumpers or extruding body work. They come in two sizes with either 3 or 6 bolt holes.

Colour: Black

Material: Tyrecord Hi-Fibre

Weight: 3.2KG


Operating temperature range: -15°C to 70°C



Unit 75, Whitehill & Bordon Enterprise Park Budds Lane, Bordon, Hampshire GU35 0FJ

Email: sales@polymax.co.uk Tel: +44 (0)1420 474 123





Rectangular Dock Bumper TPX 750L x 115W x 75H

Product SKU: 6010886

Durable Tyrecord Hi-Fibre material provides the longest lasting protection to the HGV or loading bay.

These fenders are commonly found on the HGV trailer to prevent damage to the metalwork of the vehicle. The Tyrecord Hi-Fibre material is an extremely strong and durable rubber. The thin rectangular design is a suitable shape to fix along the bumpers or extruding body work. They come in two sizes with either 3 or 6 bolt holes.

Colour: Black

Material: Tyrecord Hi-Fibre

Weight: 6.5KG

Operating temperature range: -15°C to 70°C

| Physical Property | Unit | Typical Values |
|---------------------|------|----------------|
| Hardness | ShA | 78 |
| Elongation at Break | % | 15 |
| Tensile Strength | MPa | 3.4 |

Although the technical details and recommendations made correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use Polymax products must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product. All sales subject to our standard terms www.polymax.co.uk/sales-terms